



Up to 23 SEER



evō+

The evolution of ductless split heat pump systems

Up to 23 SEER / 10 HSPF Efficiency | Inverter Technology | Modern comfort and design

www.greecomfort.com





The evō+ difference

- High Efficiency G10 Inverter Technology (Up to 23 SEER/10 HSPF)
- Stylish Design
- Gold Fin Condenser
- Photocatalytic Filter
- I-Feel Automatic Function
- Low Ambient Cooling to 5°F (208-230V systems)
- Optional GREE Tether controller
- Low voltage start-up
- Intelligent Defrost
- Intelligent Pre-heating
- Comfortable Sleep Mode
- Auto Swing (Vertical)
- Multiple Fan Speeds
- Auto Clean
- Dry Anti-mildew design
- LED display
- Automatic Operation
- Self-diagnosis
- Memory Function
- Timer
- Control lock
- Fan Delay function



Optional GREE Tether controller



Model		GWH09AB-A3DNA2B	GWH12AB-A3DNA2B	GWH09AB-D3DNA2D	GWH12AB-D3DNA2D	GWH18AC-D3DNA2D	GWH24AC-D3DNA2D
System Type		Heat Pump					
Power Supply		115V / 60Hz	115V / 60Hz	208-230V / 60Hz	208-230V / 60Hz	208-230V / 60Hz	208-230V / 60Hz
Rated Current Cooling	Amps	5.3	8.7	2.8	4.5	6.7	9.1
Rated Current Heating	Amps	6.0	10.0	3.5	5.5	7.3	13.4
System Performance							
Cooling Capacity (Min-Max)	Btu/h	9,000 (4,000-11,950)	12,000 (4,500-13,000)	9,000 (3,100-9,600)	12,000 (3,100-13,000)	18,000 (6,210-22,000)	22,000 (7,800-26,200)
Heating Capacity (Min-Max)	Btu/h	9,500 (3,412-12,500)	11,700 (3,200-14,000)	9,800 (2,200-11,000)	13,000 (2,400-14,000)	19,800 (4,100-22,000)	23,000 (6,000-26,000)
SEER/EER		23 / 14.8	22 / 12.0	23 / 14.3	22 / 12.0	18 / 12.0	18 / 12.0
HSPF/COP		9.0 / 4.0	8.9 / 3.3	9.8 / 3.6	9.1 / 3.0	10.0 / 3.5	10.0 / 3.2
Indoor Unit							
Air Flow (T/H/M/L)	CFM	306/253//218/171	330/288/253/206	306/253//218/171	330/288/253/206	488/441/383/324	610/471/412/353
Sound Pressure Level (T/H/M/L)	db(A)	42/38/30/28	47/38/30/28	46/38/30/28	48/38/30/28	46/43/40/35	51/44/40/36
Unit Dimension (WxHxD)	Inches	34.3 x 11.1 x 7	34.3 x 11.1 x 7	34.3 x 11.1 x 7	34.3 x 11.1 x 7	37.8 x 11.8 x 7.7	42.9 x 13 x 8.2
Package Dimension (WxHxD)	Inches	36.9x 14.9 x 10.8	36.9x 14.9 x 10.8	36.9 x 14.9 x 10.8	36.9 x 14.9 x 10.8	40.9 x 15.5 x 11.6	45.8 x 16.3 x 12.8
Net / Gross Weight	lb	26 / 33	26 / 33	24 / 33	24 / 33	29 / 40	35 / 46
Outdoor Unit							
Compressor Type		DC Inverter - Driven Twin Rotary					
Sound Pressure Level	db(A)	52	55	53	55	56	58
Unit Dimension (WxHxD)	Inches	33.4 x 21.3 x 12.6	33.4 x 23.2 x 12.6	33.4 x 21.3 x 12.6	33.4 x 23.2 x 12.6	37.6 x 27.6 x 15.6	38.6 x 31.1 x 16.8
Package Dimension (WxHxD)	Inches	34.7 x 23.4 x 14.3	34.7 x 25.4 x 14.3	34.7 x 23.4 x 14.3	34.7 x 25.4 x 14.3	40.5 x 29.5 x 18.0	42.6 x 33.7 x 19.2
Net / Gross Weight	lb	88 / 97	90 / 99	80 / 90	90 / 99	99 / 110	132 / 146
Refrigerant / Charge	oz.	R410A / 48.2	R410A / 48.2	R410A / 45.9	R410A / 47.6	R410A / 49.4	R410A / 56.4
Line Set Size (Liquid - Suction)	Inches	1/4" - 3/8"	1/4" - 1/2"	1/4" - 3/8"	1/4" - 1/2"	1/4" - 1/2"	1/4" - 5/8"
Pre-Charge	Feet	25	25	25	25	25	25
Max. Line Run	Feet	50	66	50	66	82	82
Max. Elevation	Feet	33	33	33	33	50	50
MCA	Amps	14	18	10	10	15	14
MOCP	Amps	20	25	15	15	25	25
Wire Size / # Wires		AWG14 / 4					



All EVO+ models



Preserving resources remains our top priority, so we've printed this piece on recycled materials.



For more information, visit greecomfort.com

est conditions are based on AHRI 210/240. Specifications are subject to change without notice. Manufacturer reserves the right to discontinue or change at any time, specifications or designs without notice or without incurring obligations. ©2013. All rights reserved. WAT120401-v3