



## PRODUCT SPECIFICATION

<b>CATALOG NUMBER:</b>	See table below			
<b>DESCRIPTION:</b>	16/2 w/gnd SPT-2 replacement power supply cord			
<b>APPROVALS:</b>	UL Listed and either CUL Listed or CSA Certified			
<b>CONSTRUCTION PARAMETERS:</b>				
Conductor:	16 AWG, 26/30 bare copper			
Conductor O.D. (nom):	0.059"			
Insulated ground conductor O.D. (nom):	0.089"			
Insulation material:	PVC, see table below for color			
Overall cable dimensions (nom):	0.154 x 0.375"			
Cord length:	See table below			
Attachment plug configuration:	NEMA 5-15P, see table below for configuration			
Plug material:	PVC, color matches cable color			
Open end configuration:	1.5" separation, 0.38" strip			
<b>ELECTRICAL PROPERTIES:</b>				
Temperature rating:	-20 to +60 °C			
Nominal operating voltage:	125 VAC			
Maximum operating current:	13 A			
Maximum operating wattage:	1625 W			
<b>CATALOG NUMBERS</b>				
	<b>Catalog number</b>	<b>Cord length</b>	<b>Color</b>	<b>Plug configuration</b>
	55233	3 ft	Black	Straight
	55234	4 ft		
	55235	5 ft		
	55236	6 ft		
	55238	8 ft		
	55243	3 ft	Gray	Right angle
	55244	4 ft		
	55245	5 ft		
	55246	6 ft		
	55248	8 ft		

The information presented here is, to the best of our knowledge, true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable Inc. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable Inc.