CR35K6-TF5

HCFC, R-22, 60 Hz, 3 -Phase, 200/230 V Air Conditioning

Production Status:

Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance			Mechanical	
Evaporator Temp. (°F)	45	45	Displacment(in^3/Rev):	3.78
Condensing Temp. (°F)	130	100	Displacment(ft^3/hr):	459.79
Return Gas Temp. (°F)	65	65	Overall Length (in):	10.23
Liquid Temp. (°F)	115	85	Overall Width (in):	9.65
Capacity (Btu/hr)	34900	46000	Overall Height (in):	14.06
Power (W):	3170	2530	Mounting Length (in):	7.50
Current (Amps):	9.60	8.20	Mounting Width (in):	7.50
EER (Btu/Wh):	11.00	18.20	Mounting Height (in):	14.44 *
Mass Flow (lbs/hr):	510	590	Suction Size (in),Type:	3/4 Stub
Sound Data @			Discharge Size (in),Type:	1/2 Stub
Sound Power (dBA):	75 Avg	80 Max	Initial Oil Charge (oz):	45
Vibration mils(peak-peak):	3.6 Avg	4.6 Max	Oil Recharge (oz):	43
Record Date:	1993-06-18		Net Weight (lbs):	74.0
			Internal Free Volume (in^3):	470.0
Electrical			Horse Power:	
LRA-High*(Amp):		75.0	*Overall compressor height on Cope	eland Brand Product's specified
LRA Low* (Amp):			mounting grommets.	
LRA-Half Winding (Amp):				
MCC (Amps):		15.97	Capacitors	
Max Operating Current(Amp):				
RLA, MCC/1.4; use for contactor selection (Amp): 11.4				
RLA, MCC/1.56;use for breake	er & wire size selection	n (Amp): 10.2		
RPM:				
UL File No:				
UL File Date:		1984-12-28		
*Low and High refer to the low which the motor is approved.	and high nominal vol	tage ranges for		
		Alterna	ate Applications	
Refrigerant	Voltage	Phase	Freq (Hz)	Application

R-22 HCFC

200/240

3

50



Air Conditioning