ZR72KCE-TF5

Copeland brand products

HCFC, R-22, 60 Hz, 3 - Phase, 200/230 V Air Conditioning

Production Status:

Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies representative for international availability.

Performance	Mechanical

Evaporator Temp. (°F)	45	45
Condensing Temp. (°F)	130	100
Return Gas Temp. (°F)	65	65
Liquid Temp. (°F)	115	85
Capacity (Btu/hr):	73500	86000
Power (W):	6250	4460
Current (Amps):	18.1	14.2
EER (Btu/Wh):	11.7	19.3
Mass Flow (lbs/hr):	1080	1110
Sound Data @		
Sound Power (dBA):	75 Avg	80 Max
Vibration mils(peak-peak):	2.0 Av	g 3.0 Max
Record Date:	2014-03-06	

Displacment (in^3/Rev):	5.98
Displacment (ft^3/hr):	727.10
Overall Length (in):	9.69
Overall Width (in):	9.69
Overall Height (in):	17.75
Mounting Length (in):	7.50
Mounting Width (in):	7.50
Mounting Height (in):	18.00 *
Suction Size (in), Type:	7/8 Stub
Discharge Size (in),Type:	1/2 Stub
Initial Oil Charge (oz):	60
Oil Recharge (oz):	56
Net Weight (lbs):	85.0
Internal Free Volume (in^3):	248.0
Horse Power:	6.00
*Overall compressor height on Copela mounting grommets.	and Brand Product's specified

Electrical Capacitors

LRA High* (Amp):	156.0
LRA Low*(Amp):	
LRA Half Winding (Amp):	
MCC (Amps):	29.0
Max Operating Current (Amp):	26.0
RLA, MCC/1.4;use for contactor selection)(Amp):	20.7
RLA, MCC/1.56;use for breaker & wire size selection)(Amp):	18.6
RPM:	3500
UL File No:	SA-2337
UL File Date:	1993-07-26
*Low and High refer to the low and high nominal voltage ranges for which th motor is approved.	

Type Part No Low MFD High MFD Volts User Description

Alternate Applications

Refrigerant	<u>Voltage</u>	Phase	Frequency	<u>Application</u>
R-134a HFC	200/220	3	50	Air Conditioning
R-134a HFC	200/230	3	60	Air Conditioning
R-22 HCFC	200/220	3	50	Air Conditioning
R-407C HFC	200/220	3	50	Air Conditioning
R-407C HFC	200/230	3	60	Air Conditioning