

**ZR94KCE-TF5**
**HFC, R-407C, 60 Hz, 3 - Phase, 200/230 V  
Air Conditioning**
**Production Status :**

Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies representative for international availability.

**Performance****Mechanical**

Evaporator Temp. (°F)	45	35	Displacement (in <sup>3</sup> /Rev):	7.76
Condensing Temp. (°F)	130	120	Displacement (ft <sup>3</sup> /hr):	942.81
Return Gas Temp. (°F)	65	55	Overall Length (in):	10.38
Liquid Temp. (°F)	115	105	Overall Width (in):	11.23
Capacity (Btu/hr):	94000	81200	Overall Height (in):	18.75
Power (W):	8310	7330	Mounting Length (in):	7.50
Current (Amps):	25.6	23.4	Mounting Width (in):	7.50
EER (Btu/Wh):	11.3	11.1	Mounting Height (in):	19.50 *
Mass Flow (lbs/hr):	1370	1135	Suction Size (in),Type:	1 1/8 Stub
<u>Sound Data @</u>			Discharge Size (in),Type:	7/8 Stub
Sound Power (dBA):	79 Avg	84 Max	Initial Oil Charge (oz):	85
Vibration mils(peak-peak):	3.0 Avg	4.5 Max	Oil Recharge (oz):	81
Record Date:	2016-06-24		Net Weight (lbs):	125.0
			Internal Free Volume (in <sup>3</sup> ):	639.0
			Horse Power:	8.00
			*Overall compressor height on Copeland Brand Product's specified mounting grommets.	

**Electrical****Capacitors**

LRA High* (Amp):	195.0	<u>Type</u>	<u>Part No</u>	<u>Low MFD</u>	<u>High MFD</u>	<u>Volts</u>	<u>User Description</u>
LRA Low*(Amp):							
LRA Half Winding (Amp):							
MCC (Amps):	45.0						
Max Operating Current (Amp):	31.8						
RLA, MCC/1.4;use for contactor selection)(Amp):	32.1						
RLA, MCC/1.56;use for breaker & wire size selection)(Amp):	28.8						
RPM:	3500						
UL File No:	SA-2337						
UL File Date:	1996-09-27						
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.							

**Alternate Applications**

<u>Refrigerant</u>	<u>Voltage</u>	<u>Phase</u>	<u>Frequency</u>	<u>Application</u>
R-134a HFC	200/220	3	50	Air Conditioning
R-134a HFC	200/230	3	60	Air Conditioning
R-407C HFC	200/220	3	50	Air Conditioning