ZR94KCE-TF5

HFC, R-407C, 60 Hz, 3 -Phase, 200/230 V

Air Conditioning

Production Status:

Available for sale to all U.S. customers. Please check with your local Emerson Climate

Technologies Representative for international availability.

Performance

Evaporator Temp. (°F)	45	35
Condensing Temp. (°F)	130	120
Return Gas Temp. (°F)	65	55
Liquid Temp. (°F)	115	105
Capacity (Btu/hr)	94000	81200
Power (W):	8310	7330
Current (Amps):	25.60	23.40
EER (Btu/Wh):	11.30	11.10
Mass Flow (lbs/hr):	1370	1135
Sound Data @		
Sound Power (dBA):	79 Avg	84 Max
Vibration mils(peak-peak):	3.0 Avg	4.5 Max
Record Date:	2016-06-24	

Flectrical

Electrical					
LRA-High*(Amp):	195.0				
LRA Low* (Amp):					
LRA-Half Winding (Amp):					
MCC (Amps):	45.0				
Max Operating Current(Amp):	31.8				
RLA, MCC/1.4;use for contactor selection (Amp):	32.1				
RLA, MCC/1.56;use for breaker & wire size selection (Amp):	28.8				
RPM:	3500				
UL File No: SA-233					
UL File Date: 1996-09-					
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

Mechanical

Displacment(in^3/Rev):	7.76	
Displacment(ft^3/hr):	942.81	
Overall Length (in):	10.38	
Overall Width (in):	11.23	
Overall Height (in):	18.75	
Mounting Length (in):	7.50	
Mounting Width (in):	7.50	
Mounting Height (in):	19.50 *	
Suction Size (in),Type:	1 1/8 Stub	
Discharge Size (in),Type:	7/8 Stub	
Initial Oil Charge (oz):	85	
Oil Recharge (oz):	81	
Net Weight (lbs):	125.0	
Internal Free Volume (in^3):	639.0	
Horse Power:	8.00	
*Overall compressor height on Copeland Brand Product's specified mounting grommets.		

Capacitors

Alternate Applications

• •				
Refrigerant	<u>Voltage</u>	<u>Phase</u>	Freq (Hz)	<u>Application</u>
R-134a HFC	200/220	3	50	Air Conditioning
R-134a HFC	200/230	3	60	Air Conditioning
R-407C HFC	200/220	3	50	Air Conditioning