

EZWELD® 777 THREAD SEALANT WITH PTFE/WHITE

LOW VOC

GENERAL DESCRIPTION

E-Z Weld 777 Thread Sealant with PTFE is a specially formulated NON-TOXIC compound consistently provides a leak-proof joint. This product is made with virgin PTFE thus assuring maximum performance. Unlike other thread sealants, 777 will not dry or harden. It's consistency is smooth and paste like. It flows nicely

APPLICATION:

777 Thread Sealant is approved for all types of plastic and metal pipes and fittings. It may be used on PVC, CPVC, ABS, Copper, Steel, Galvanized, brass, iron, aluminum or stainless steel pipes. Do not use on oxygen systems or with oxygenated solvents.

Always follow instructions on the label.

Application temperature: -50° F to 500° F (-46° to 260°C)

Storage temperature: 10°F to 120° F (-12° to 49°C)

Working Pressure: 300 psi for gas, 10,000 psi for liquids



CERTIFICATION:



This product is tested, certified and approved by NSF International for use on drain, waste and potable water systems. It is also listed by the International Association of Plumbing & Mechanical Officials (IAPMO). It carries the Uniform Plumbing Code (UPC) seal. This sealant meets ASTM Standard D6396.



PW, DWV, SW

QUALITY ASSURANCE:

Every batch of thread sealant is carefully checked and monitored to assure consistently high quality standard. All ingredients are purchased from approved suppliers.

PHYSICAL PROPERTIES:

Color: White

Body: Paste Like

Set: Soft

Shelf Life: 3 years (unopened can)

AVAILABILITY:

Size	Part No. Regular	(UPC No.)	
1/4 Pt	EZ77701	812574011425	<i>1/4 pt., 1/2 pt., Pt., Qt. cans are supplied with dauber inside cap.</i>
1/2 Pt	EZ77702	812574011432	
Pt	EZ77703	812574011449	
Qt	EZ77704	812574012286	

E-ZWELD® 777 THREAD SEALANT WITH PTFE/WHITE

LOW
VOC

PACKAGING:

Size	¼ Pt	½ Pt	Pt	Qt
Fluid oz	4	8	16	32
Liters	0.12	0.24	0.47	0.95
Units per case	24	24	12	12
Weight per case - Lb.	9.5	16	15.5	28
Weight per case - Kg	4.32	7.27	7.05	12.73
Cubic feet per case	0.260	0.420	0.404	0.762
Cubic meter per case	0.007	0.012	0.011	0.022
Cases per pallet	145	90	88	56

Note: Packaging sizes subject to availability. Please check with your distributor or contact E-ZWELD.

SAFETY PRECAUTIONS:

Keep in a cool place, out of reach of children. Keep container tightly closed when not in use. Avoid contact with skin and eyes. Dispose of material and container in a safe way. Do not empty into drains, storm drains or watercourses. Wear suitable gloves and eye protection. If seeking medical advice show physician label or SDS. Use only in well ventilated areas.

Inhalation: Remove to fresh air. If breathing is stopped, give artificial respiration. If breathing is difficult, give Oxygen. Seek medical advice.

Eyes: Flush eyes immediately with plenty of water for 15 minutes and seek medical advice immediately.

Internal: If swallowed give 1 or 2 glasses of water immediately, call physician, hospital or poison control immediately. **DO NOT INDUCE VOMITING.**

SHIPPING/ TRANSPORTATION:

Material packaged in less than a liter size is exempted under "Limited Quantity Rules" by DOT. These packages may be shipped with the description ORM - D Consumer Commodity. Packages shipped under this description are not subject to shipping paper requirements for flammable materials.