

# Submittal Data: System 18CL ASU18CL & AOU18CL



Job Name:	Location:	
Purchaser:		
Engineer:		
Submitted To:	For:	<input type="checkbox"/> Reference <input type="checkbox"/> Approval <input type="checkbox"/> Construction
Submitted By:		
Unit Designation:	Schedule No.	Model No.:

### Capacities:

Cooling	18,000 BTU/h
Outdoor Design Temperature <i>F° DB/WB</i>	95/75
SEER	19.0
EER	10.4

### Indoor Unit:

Power Supply	230 V
Noise Level Cooling <i>db (A) - H/ M/ L/ Q</i>	44/38/32/25
Weight	20 lbs.

### Outdoor Unit:

Power Supply	230 V
Recommended Fuse Size	20A
Min. Ampacity	16A
Running Current <i>Cooling</i>	7.7A
Weight	88 lbs.

### Refrigerant Piping:

Max Ht. Difference	49 ft.
Max Total or Combined Length	66 ft.
Discharge Vapor Line (O.D.)	1/4 in.
Suction (O.D.)	1/2 in.

### Standard Features:

- |  |  |  |
|--|--|--|
| <ul style="list-style-type: none"> <li>◆ Six year compressor warranty</li> <li>◆ Two year parts warranty</li> <li>◆ Digital wireless remote control</li> <li>◆ Auto Mode</li> <li>◆ Auto Louver: Up/Down</li> <li>◆ Apple Catechin Filter</li> </ul> | <ul style="list-style-type: none"> <li>◆ Sleep timer</li> <li>◆ Built in Low Ambient</li> <li>◆ Auto Restart/ Reset</li> <li>◆ 24 hour timer</li> <li>◆ Cold Prevention</li> <li>◆ Ion Deodorizing Filter</li> </ul> | <ul style="list-style-type: none"> <li>◆ Optional Wired Remote Control</li> <li>◆ Dry mode</li> <li>◆ Refrigerant R410A</li> <li>◆ Quiet Mode</li> <li>◆ Auto Changeover</li> <li>◆ Coil Dry Mode</li> </ul> |
|--|--|--|

### Notes:

---



---



---

### OUTLINE AND DIMENSIONS

