

Submittal Data: System 42RCLX AUU42RCLX & AOU42RLX



Job Name: _____ Location: _____

Purchaser: _____

Engineer: _____

Submitted To: _____ For: Reference Approval Construction

Submitted By: _____

Unit Designation: _____ Schedule No. _____ Model No.: _____

Capacities:

Cooling	42,700/45,000 BTU/h
Outdoor Design Temperature <i>F^o</i> DB/WB	95/75
Heating	47,800/54,000 BTU/h
Outdoor Design Temperature <i>F^o</i> DB/WB	47/43
SEER	15.0
EER <i>Clg/Htg</i>	9.2/10.5

Indoor Unit:

Power Supply	230 V
Noise Level Cooling <i>db (A) - H/ M/ L/</i>	50/48/44
Noise Level Heating <i>db (A) - H/ M/ L/</i>	50/48/44
Weight	88 lbs.

Outdoor Unit:

Power Supply	230 V
Recommended Fuse Size	30A
Min. Ampacity	26A
Running Current <i>Cooling</i>	20.3/21.7A
Running Current <i>Heating</i>	19.1/21.7A
Weight	231 lbs.

Refrigerant Piping:

Max Ht. Difference	98/30 ft.
Max Total or Combined Length	230 ft. each
Discharge Vapor Line (O.D.)	3/8 in.
Suction (O.D.)	5/8 in.

Standard Features:

- | | | |
|--------------------------------|------------------------|--------------------------------------|
| ◆ Six year compressor warranty | ◆ Slender fit | ◆ Full Function Wired Remote Control |
| ◆ Two year parts warranty | ◆ Built in Low Ambient | ◆ Dry mode |
| ◆ Weekly timer | ◆ Auto Restart/ Reset | ◆ Refrigerant R410A |
| ◆ Auto Louver: Up/Down | ◆ Auto Mode | ◆ Quiet Mode |
| ◆ Energy saver | ◆ High Ceiling Mode | ◆ Cold Prevention |
| ◆ Pump Down Operation | ◆ Branch Duct Capable | |

Notes:

OUTLINE AND DIMENSIONS

