

Description:

XR3 series mechanical brass fittings are specifically designed for use with Gastite® and FlashShield™ flexible gas piping systems complying with ANSI LC 1 "Fuel Gas Piping Systems Using CSST". The self-flaring fitting produces a metal-to-metal seal, and is reusable. The fittings have standard NPT threads and may be used in combination with all approved fuel gas piping materials with pipe thread as an interface. The Jacket-Lock™ and Shield-to-fitting features provide CSST protection.

Components:

- Male NPT Adapter, Split Bushings, Termination Nut, Corrosion Resistant Steel Flange

Features:

- Tool-Less Flare Fitting Design
- Metal-to-Metal Seal
- Multi-Point Seal
- Jacket-Lock™
- Shield-to-fitting
- Fully Reusable Fitting
- Approved for Outdoor and Concealed Use

Listings:

- CSA Certificate 2728525
- ICC-ES Report No. PMG 1155 and PMG 1019
- IAPMO: File No. 3250 and Report No. 0239



Technical Data:

Max. Approved Operating Pressure	25 psi
Operating Temperature Range	-40°F to 160°F
Fitting Material	CA360 Brass

Dimensional Characteristics

Size	P/N	Pipe Thread	Flange Thread	Nut Hex	Fitting Hex	Flange O.D.	Mounting Hole Pattern (dia.)	Reference Assembly Torque (ft-lbs)
1/2"	XR3TRM-8	1/2"	3/4"	1-1/4"	1-1/8"	2-5/8"	2-3/4"	35
3/4"	XR3TRM-11	3/4"	1"	1-9/16"	1-3/8"	2-5/8"	2-3/4"	45
1"	XR3TRM-16	1"	1-1/4"	1-15/16"	1-3/4"	2-5/8"	2-3/4"	65
1-1/4"	XR3TRM-20	1-1/4"	1-1/2"	2-3/16"	2-1/16"	3-1/4"	3-1/4"	95
1-1/2"	XR3TRM-24	1-1/2"	2"	2-1/2"	2-5/16"	3-1/4"	3-1/4"	120
2"	XR3TRM-32	2"	2-1/2"	3-1/8"	2-15/16"	3-5/8"	4"	150