

| | | | |
|--|--|--|-------------|
| Submittal Data: CAS24HP230V1AC | | 24,000 BTU/H Ceiling Cassette | |
| Job Name | | Location | Date |
| Purchaser | | Engineer | |
| Submitted To | | For <input type="checkbox"/> Reference <input type="checkbox"/> Approval <input type="checkbox"/> Construction | |
| Unit Designation | | Schedule No. | |
| GENERAL FEATURES -Quiet Operation -Multi-Speed Fan -4-way Discharge Air -Internal Condensate Drain Pump -Swing Louver -Both Wireless & Wired Remote Controllers -Power Failure Recovery -Sentry Condensate Overflow Protection -Decorative Grille (Sold Separately) -Limited 5 yr. Parts Warranty | | | |
| System Ratings | | Units Specification & Data | |
| Cooling* Rated Capacity 22,800 BTU/H | | Wired Controller XK-19 | |
| Heating* Rated Capacity 27,400 BTU/H | | Air Filter Netted polypropylene | |
| Sound Pressure (Hi/Lo)** Cooling 49/45 dbA Heating 49/45 dbA | | Condensate Drain Lift (Height) 12-in 305-mm | |
| Air Flow (min/max) Indoor Fan 500/694 CFM | | Drain Size (OD) 1.2-in 31-mm | |
| Electrical Ratings | | Refrigerant Piping Data | |
| Fan Motor Output Power 50 W FLA 0.4 A | | Refrigerant Type R410A | |
| Power Supply Normal Operational Voltage 208/230 V, 1 Phase, 60 Hz Voltage Range 187 - 253 V MCA 1.0 A Interconnecting Cable Wire Size 14-4 AWG | | Gas Pipe Size (OD) 5/8-in Liquid Pipe Size (OD) 3/8-in Connection Method Flared | |
| | | * Test conditions are based on AHRI 210/240. **Sound Power ratings are per AHRI 270 and AHRI 350 | |



