

WIFI
CAPABLE
(SELECTED MODELS)

livo+



Inverter Driven Mini Split
Heat Pump

High Efficiency
G10 Inverter Technology
Quiet Comfort

 **GREE**

www.greecomfort.com

LIVO+



I Feel

Senses temperatures surrounding the remote control to adjust airflow and indoor temperature.



Hidden Display



LIVO+ Series Heat Pump Difference

G10 Inverter Technology
Multiple Fan Speeds
Self-Diagnostics
Low Voltage Start-Up
Selectable Dry Mode

Intelligent Defrost
Comfortable Sleep Mode
Auto Restart
Vertical Swing Louvers
Backlight Display

Programmable Timer
Control Lock
Blue Fin Condenser Coil
Automatic Operation
XK-41 Wired Controller (optional)

Universal WIFI Kit
Part No. WSBE02
(sold separately)

Use Part No. WSBE03 for
LIVS09HP115V1B only

MODELS		LIVS09HP115V1B	LIVS12HP115V1B	LIVS09HP230V1B	LIVS12HP230V1B	LIVS18HP230V1B	LIVS24HP230V1B	LIVS30HP230V1B*	LIVS36HP230V1B&C*	
System Type		HEAT PUMP								
		SYSTEM PERFORMANCE								
Cooling Capacity (min-max)	Btu/h	9,000 (2,764-10,918)	12,000 (3,753-12,500)	9,000 (3,100-9,600)	12,000 (3,753-12,500)	18,000 (7,165-20,001)	22,000 (8,630-23,200)	28,000 (9,500-30,000)	33,600 (7,400-36,000)	
Heating Capacity (min-max)	Btu/h	9,600 (2,081-12,283)	13,000 (3,412-15,013)	9,500 (3,100-12,000)	13,000 (3,924-14,000)	19,000 (7,336-23,498)	23,000 (8,650-26,000)	28,400 (10,000-33,000)	34,600 (15,000-36,000)	
SEER/EER		16/9.55	16/10.55	16/10.0	16/9.25	16/9.0	16/9.75	16/9.3	16/8.2	
HSPF/COP		9.0/3.3	9.0/3.1	9.0/3.5	9.0/3.1	9.0/2.8	9.0/2.9	8.2/3.0	8.2/2.7	
Energy Star®		No								
Cooling Temperature Range	°F	0 - 115	0 - 115	0 - 115	0 - 115	0 - 115	0 - 115	0 - 109	0 - 109	
Heating Temperature Range	°F	-4 - 75	-4 - 75	-4 - 75	-4 - 75	-4 - 75	-4 - 75	-4 - 75	-4 - 75	
		INDOOR UNIT								
Air flow (min-max)	CFM	171-318	194-400	171-318	194-400	282-471	530-706	412-706	412-736	
Sound Level (min-max)	dB(A)	28-42	29-43	28-43	29-45	35-46	36-48	41-56	41-56	
Dehumidification	pt/hr	1.7	3.0	1.7	3.0	3.8	5.3	6.3	7.4	
Unit Dimension (WxHxD)	in	31.1 x 10.8 x 7.9	33.3 x 11.4 x 8.3	31.1 x 10.8 x 7.9	33.3 x 11.4 x 8.3	38.2 x 11.8 x 8.8	42.4 x 12.8 x 9.7	53.2 x 12.8 x 10.0	53.2 x 12.8 x 10.0	
Package Dimension (WxHxD)	in	34.0 x 13.9 x 10.6	36.1 x 14.3 x 10.9	34.0 x 13.9 x 10.6	36.1 x 14.3 x 10.9	40.9 x 15.0 x 12.0	45.1 x 16.1 x 13.2	56.6 x 16.5 x 13.5	56.6 x 16.5 x 13.5	
Weight (Net/Gross)	lbs	19.8 / 24.3	22.1 / 27.6	19.8 / 24.3	23.2 / 28.7	29.8 / 36.4	37.5 / 45.2	41.9 / 57.3	41.9 / 57.3	
		OUTDOOR UNIT								
Compressor Type		G10 INVERTER DRIVEN ROTARY								
Sound Level	dB(A)	53	53	52	53	56	59	62	65	
Unit Dimension (WxHxD)	in	33.4 x 21.3 x 12.6	33.4 x 21.3 x 12.6	30.6 x 21.3 x 12.6	30.6 x 21.3 x 12.6	39.4 x 31.2 x 16.8	38.0 x 27.6 x 15.3	39.4 x 31.2 x 16.8	39.4 x 31.2 x 16.8	
Package Dimension (WxHxD)	in	34.6 x 22.6 x 14.2	34.6 x 22.8 x 14.2	32.3 x 22.8 x 14.0	33.4 x 22.8 x 14.2	40.4 x 29.0 x 17.9	40.4 x 29.0 x 17.9	42.5 x 33.1 x 19.1	42.5 x 33.1 x 19.1	
Weight (Net/Gross)	lbs	62.8 / 68.4	67.3 / 72.8	66.2 / 71.7	69.5 / 75.0	95.9 / 105.8	110.3 / 120.2	154.4 / 163.2	161.0 / 169.8	
Refrigerant Charge - R410A	oz	24.7	31.8	24.7	30.0	49.4	65.3	84.7	91.7	
Coil Type		Copper / Aluminum with BLUE FIN Coating								
		INSTALLATION								
Line Set Size (Liquid - Gas)	in	1/4 - 3/8	1/4 - 3/8	1/4 - 3/8	1/4 - 3/8	1/4 - 1/2	1/4 - 5/8	1/4 - 5/8	1/4 - 5/8	
Pre-Charge Length	ft	25	25	25	25	25	25	25	25	
Max. Line Run	ft	49	66	49	66	82	82	98	98	
Max. Elevation	ft	33	33	33	33	33	33	33	33	
		ELECTRICAL								
Voltage / Phase / Hertz		115V /1/ 60Hz	115V /1/ 60Hz	208-230V /1/ 60Hz	208-230V /1/ 60Hz	208-230V /1/ 60Hz	208-230V /1/ 60Hz	208-230V /1/ 60Hz	208-230V /1/ 60Hz	
Rated Current Cooling	amps	11.3	13.0	5.8	6.0	11.5	12.0	17.0	20.0	
Rated Current Heating	amps	10.7	13.2	6.0	6.7	11.5	12.2	17.5	20.0	
MCA	amps	17	20	9	9	16	16	20	24	
MOCP	amps	25	30	15	15	25	25	30	40	
Interconnecting Wire		AWG14 / 4	AWG14 / 4	AWG14 / 4	AWG14 / 4	AWG14 / 4	AWG14 / 4	AWG14 / 4	AWG14 / 4	
Limited Warranty		5 Years on Parts								

* Model can not be upgraded with WIFI.



Specifications are subject to change without notice. Manufacturer reserves the right to discontinue or change at any time, specifications or designs without notice or without incurring obligations.

©2018. All rights reserved.

Contact No. GREE_LIVO+_BROCHURE_050119



SCAN TO LEARN MORE ABOUT
GREE PRODUCTS OR VISIT US AT
GREECOMFORT.COM