

TEK-Mate®

REFRIGERANT LEAK DETECTOR

Find leaks fast.

Affordable price, simple operation, and reliable performance make TEK-Mate the refrigerant leak detector of choice for thousands of technicians. See for yourself why TEK-Mate is the #1 selling refrigerant leak detector in the HVAC/R market.

Leak Detector Selection Guide on page 19



SAE J1627



ADVANTAGES

- ▀ Sensitivity of 0.25 oz./year (7 g/year)
- ▀ Detects all CFCs, HCFCs, HFCs, and HFOs
- ▀ Proven heated diode sensor for reliable leak checking
- ▀ No false alarms from soap solutions
- ▀ Runs on two D-cell batteries
- ▀ Rugged carrying case included

SPECIFICATIONS

Includes	TEK-Mate Heated diode sensor Two D-size alkaline batteries Spare filters Carrying case
Compatible refrigerants	R22, R32, R134a, R404a, R407c, R410a, R422b, R448a, R449a, R452a, R452b, R507 (AZ50), R1234yf and more
Minimum sensitivity	0.25 oz./yr. (7 g/yr.)
Sensitivity per EN14624	2 g/yr.
Power source	Two D-size alkaline batteries
Battery life	16 hours
Weight	1.54 lb. (700 g)
Certifications	CE SAEJ1627 EN14624:2012 A2L certified
Probe length	15 in. (38 cm)
Warranty	Two-year over-the-counter

ORDERING INFORMATION

TEK-Mate	705-202-G1
----------	------------

Accessories and Replacement Parts

TEK-Check R134a reference leak	703-080-G10
Sensor	703-020-G1
Filters	705-600-G1
Carrying case	705-700-G1



WARNING: This product can expose you to chemicals including butadiene, which is known to the State of California to cause cancer and reproductive harm. For more information, go to www.P65Warnings.ca.gov.