



Your Single Source Solution

Standard EZ-Pull® Line Sets for HVACR Applications

Split system (A/C & Heat Pump).

<u>Job Name</u>	<u>Contractor</u>
<u>Job Location</u>	<u>Wholesaler</u>
<u>Engineer</u>	<u>JMF Rep</u>

APPLICATION - FEATURES

- Meets ASTM E84 for smoke and fire (25/50)
- Rugged, anti-tear exterior allows for easier installation of the line set
- R410 A Approved
- Paintable: For maximum longevity, insulation material must be either painted or jacketed where outdoor environmental exposure is present.
- Superior tear resistance
- UV Resistant
- Insulation is marked every foot

TECHNICAL SPECIFICATIONS

Copper Tubing: Commercial Grade Refrigeration Tubing (ASTM B743 & ASTM B88)
 Copper: No. C122200 DHP (Phosphorous deoxidized, high residual phosphorous)
 Low-density Polyethylene Foam: Closed cells foam, CFC and HCFC gas free
 Insulation: According to ASTM E96-00
 Working Temperature: Meets/exceeds ASTM C 1427-07
 Surface Burning Characteristics: UL 94HBT, UL 723, ASTM E84 (25/50), flame and spread index less than 25 and smoke development index less than 50 as tested according to UL 723.

EZ-Pull - Insulation (White Hard Shell):
 Uninsulated Liquid Line
 Insulated Suction Line
 Tube Size: 1/4" - 1 1/8"
 Lengths: 10' - 100'
 Insulation Wall Thickness: 1/2" & 3/4"

INSULATION R VALUES

1/2" Wall - R3.3
 3/4" Wall - R5.2
 *R - Value calculation using a K-Factor of 0.25
 BTU-in/hr-ft (2)-F @ 75°F, 24°C mean temp.

JMF COMPANY IS YOUR CONSOLIDATING SOURCE FOR copper tubing, line sets, copper fittings, push to fit, pex, ball valves, gas valves, plumbing valves, malleable fittings, steel nipples, plastic fittings, brass threaded, brass nipples, flare & compression, gas connectors, water connectors, appliance kits, cord sets and MORE.

