

VG1000 Series Two-Way, Stainless Steel Trim, NPT End Connections Ball Valves with Spring Return Electric Actuators with Switches

Description

VG1000 Series Ball Valves are designed to regulate the flow of hot or chilled water and, for some models, low pressure steam in response to the demand of a controller in Heating, Ventilating, and Air Conditioning (HVAC) systems. Available in sizes 1/2 through 2 in. (DN15 through DN50), this family of two- and three-way forged brass valves is factory or field mounted to Johnson Controls® VA9104, M9106, M9109, and M9100 Series Non-Spring Return and VA9203 and VA9208 Series Spring Return Electric Actuators for on/off, floating, or proportional control.

Refer to the *VG1000 Series Forged Brass Ball Valves Product Bulletin (LIT-977132)* for important product application information.

Features

- forged brass body — provides 580 psig static pressure rating
- graphite-reinforced Polytetrafluoroethylene (PTFE) seats — include 15% graphite-reinforced ball seals, providing better wear resistance
- 500:1 rangeability — provides accurate control under all load conditions
- maintenance-free design — performs without failure in excess of 200,000 full stroke cycles in iron-oxide contaminated water



VG1000 Series Two-Way, Spring Return, Stainless Steel Ball and Stem Ball Valve Assemblies with End Switches

Repair Information

If the VG1000 Series Ball Valve fails to operate within its specifications, replace the unit. For a replacement valve, contact the nearest Johnson Controls representative.

Selection Charts

Two-Way – Spring Return Valve Open – Normally Open with Switches (Not Rated for Steam Service)

| Fluid Temperatures: -22 to 212°F (-30 to 100°C) Not Rated for Steam Service | | | | AC 24 V | | | AC 85–264 V (VA9203) AC 120 V (VA9208) |
|---|-----------|-------------------|---------------|--|---------------------------|-----------------|---|
| Valve | Size, in. | Cv | Closeoff psig | Floating | DC 0 to 10 V Proportional | On/Off | On/Off |
| | | | | Spring Return Open — Valve Normally Open — Actuators with One Switch | | | |
| | | | | VA9203-AGB-ZZ | VA9203-GGB-ZZ | VA9203-BGB-2 | VA9203-BUB-2 |
| VG1245AD | 1/2 | 1.2 ¹ | 200 | VG1245AD+923AGB | VG1245AD+923GGB | VG1245AD+923BGB | VG1245AD+923BUB |
| VG1245AE | | 1.9 ¹ | | VG1245AE+923AGB | VG1245AE+923GGB | VG1245AE+923BGB | VG1245AE+923BUB |
| VG1245AF | | 2.9 ¹ | | VG1245AF+923AGB | VG1245AF+923GGB | VG1245AF+923BGB | VG1245AF+923BUB |
| VG1245AG | | 4.7 ¹ | | VG1245AG+923AGB | VG1245AG+923GGB | VG1245AG+923BGB | VG1245AG+923BUB |
| VG1245AL | | 7.4 ¹ | | VG1245AL+923AGB | VG1245AL+923GGB | VG1245AL+923BGB | VG1245AL+923BUB |
| VG1245AN | | 11.7 | | VG1245AN+923AGB | VG1245AN+923GGB | VG1245AN+923BGB | VG1245AN+923BUB |
| VG1245BG | 3/4 | 4.7 ¹ | 200 | VG1245BG+923AGB | VG1245BG+923GGB | VG1245BG+923BGB | VG1245BG+923BUB |
| VG1245BL | | 7.4 ¹ | | VG1245BL+923AGB | VG1245BL+923GGB | VG1245BL+923BGB | VG1245BL+923BUB |
| VG1245BN | | 11.7 | | VG1245BN+923AGB | VG1245BN+923GGB | VG1245BN+923BGB | VG1245BN+923BUB |
| VG1245CL | 1 | 7.4 ¹ | 200 | VG1245CL+923AGB | VG1245CL+923GGB | VG1245CL+923BGB | VG1245CL+923BUB |
| VG1245CN | | 11.7 ¹ | | VG1245CN+923AGB | VG1245CN+923GGB | VG1245CN+923BGB | VG1245CN+923BUB |
| VG1245CP | | 18.7 | | VG1245CP+923AGB | VG1245CP+923GGB | VG1245CP+923BGB | VG1245CP+923BUB |
| Valve | Size, in. | Cv | Closeoff psig | Spring Return Open — Valve Normally Open — Actuators with Two Switches | | | |
| | | | | VA9208-AGC-3 | VA9208-GGC-3 | VA9208-BGC-3 | VA9208-BAC-3 |
| VG1245DN | 1-1/4 | 11.7 ¹ | 200 | VG1245DN+938AGC | VG1245DN+938GGC | VG1245DN+938BGC | VG1245DN+938BAC |
| VG1245DP | | 18.7 ¹ | | VG1245DP+938AGC | VG1245DP+938GGC | VG1245DP+938BGC | VG1245DP+938BAC |
| VG1245DR | | 29.2 | | VG1245DR+938AGC | VG1245DR+938GGC | VG1245DR+938BGC | VG1245DR+938BAC |
| VG1245EP | 1-1/2 | 18.7 ¹ | 200 | VG1245EP+938AGC | VG1245EP+938GGC | VG1245EP+938BGC | VG1245EP+938BAC |
| VG1245ER | | 29.2 ¹ | | VG1245ER+938AGC | VG1245ER+938GGC | VG1245ER+938BGC | VG1245ER+938BAC |
| VG1245ES | | 46.8 | | VG1245ES+938AGC | VG1245ES+938GGC | VG1245ES+938BGC | VG1245ES+938BAC |
| VG1245FR | 2 | 29.2 ¹ | 200 | VG1245FR+938AGC | VG1245FR+938GGC | VG1245FR+938BGC | VG1245FR+938BAC |
| VG1245FS | | 46.8 ¹ | | VG1245FS+938AGC | VG1245FS+938GGC | VG1245FS+938BGC | VG1245FS+938BAC |
| VG1245FT | | 73.7 | | VG1245FT+938AGC | VG1245FT+938GGC | VG1245FT+938BGC | VG1245FT+938BAC |

1. Cv has a characterizing disk.



VG1000 Series Two-Way, Stainless Steel Trim, NPT End Connections Ball Valves with Spring Return Electric Actuators with Switches (Continued)

Two-Way – Spring Return Closed – Valve Normally Closed

| Fluid Temperatures: -22 to 212°F (-30 to 100°C) Not Rated for Steam Service | | | | AC 24 V | | | AC 85–264 V (VA9203) AC 120 V (VA9208) |
|---|-----------|-------------------|---------------|--|---------------------------|------------------|---|
| Valve | Size, in. | Cv | Closeoff psig | Floating | DC 0 to 10 V Proportional | On/Off | On/Off |
| | | | | Spring Return Closed — Valve Normally Closed — Actuators with One Switch | | | |
| | | | | VA9203-AGB-2Z | VA9203-GGB-2Z | VA9203-BGB-2 | VA9203-BUB-2 |
| VG1245AD | 1/2 | 1.2 ¹ | 200 | VG1245AD+943AGB | VG1245AD+943GGB | VG1245AD+943BGB | VG1245AD+943BUB |
| VG1245AE | | 1.9 ¹ | | VG1245AE+943AGB | VG1245AE+943GGB | VG1245AE+943BGB | VG1245AE+943BUB |
| VG1245AF | | 2.9 ¹ | | VG1245AF+943AGB | VG1245AF+943GGB | VG1245AF+943BGB | VG1245AF+943BUB |
| VG1245AG | | 4.7 ¹ | | VG1245AG+943AGB | VG1245AG+943GGB | VG1245AG+943BGB | VG1245AG+943BUB |
| VG1245AL | | 7.4 ¹ | | VG1245AL+943AGB | VG1245AL+943GGB | VG1245AL+943BGB | VG1245AL+943BUB |
| VG1245AN | | 11.7 | | VG1245AN+943AGB | VG1245AN+943GGB | VG1245AN+943BGB | VG1245AN+943BUB |
| VG1245BG | 3/4 | 4.7 ¹ | 200 | VG1245BG+943AGB | VG1245BG+943GGB | VG1245BG+943BGB | VG1245BG+943BUB |
| VG1245BL | | 7.4 ¹ | | VG1245BL+943AGB | VG1245BL+943GGB | VG1245BL+943BGB | VG1245BL+943BUB |
| VG1245BN | | 11.7 | | VG1245BN+943AGB | VG1245BN+943GGB | VG1245BN+943BGB | VG1245BN+943BUB |
| VG1245CL | 1 | 7.4 ¹ | 200 | VG1245CL+943AGB | VG1245CL+943GGB | VG1245CL+943BGB | VG1245CL+943BUB |
| VG1245CN | | 11.7 ¹ | | VG1245CN+943AGB | VG1245CN+943GGB | VG1245CN+943BGB | VG1245CN+943BUB |
| VG1245CP | | 18.7 | | VG1245CP+943AGB | VG1245CP+943GGB | VG1245CP+924TBGB | VG1245CP+943BUB |
| Valve | Size, in. | Cv | Closeoff psig | Spring Return Closed — Valve Normally Closed — Actuators with Two Switches | | | |
| | | | | VA9208-AGC-3 | VA9208-GGC-3 | VA9208-BGC-3 | VA9208-BAC-3 |
| VG1245DN | 1-1/4 | 11.7 ¹ | 200 | VG1245DN+958AGC | VG1245DN+958GGC | VG1245DN+958BGC | VG1245DN+958BAC |
| VG1245DP | | 18.7 ¹ | | VG1245DP+958AGC | VG1245DP+958GGC | VG1245DP+958BGC | VG1245DP+958BAC |
| VG1245DR | | 29.2 | | VG1245DR+958AGC | VG1245DR+958GGC | VG1245DR+958BGC | VG1245DR+958BAC |
| VG1245EP | 1-1/2 | 18.7 ¹ | 200 | VG1245EP+958AGC | VG1245EP+958GGC | VG1245EP+958BGC | VG1245EP+958BAC |
| VG1245ER | | 29.2 ¹ | | VG1245ER+958AGC | VG1245ER+958GGC | VG1245ER+958BGC | VG1245ER+958BAC |
| VG1245ES | | 46.8 | | VG1245ES+958AGC | VG1245ES+958GGC | VG1245ES+958BGC | VG1245ES+958BAC |
| VG1245FR | 2 | 29.2 ¹ | 200 | VG1245FR+958AGC | VG1245FR+958GGC | VG1245FR+958BGC | VG1245FR+958BAC |
| VG1245FS | | 46.8 ¹ | | VG1245FS+958AGC | VG1245FS+958GGC | VG1245FS+958BGC | VG1245FS+958BAC |
| VG1245FT | | 73.7 | | VG1245FT+958AGC | VG1245FT+958GGC | VG1245FT+958BGC | VG1245FT+958BAC |

1. Cv has a characterizing disk.



VG1000 Series Two-Way, Stainless Steel Trim, NPT End Connections Ball Valves with Spring Return Electric Actuators with Switches (Continued)

Valve Assemblies with M9000-561 Thermal Barrier Installed — Rated for High Temperature Fluid Service, Two-Way – Spring Return – With End Switches

| Fluid Temperatures: -22 to 284°F (-30 to 140°C), 15 psi Steam | | | | AC 24 V | | | AC 85–264 V (VA9203) AC 120 V (VA9208) |
|--|-----------|-------------------|---------------|----------------------|---------------------------|-----------------------------|---|
| Valve | Size, in. | Cv | Closeoff psig | Floating | DC 0 to 10 V Proportional | On/Off | On/Off |
| | | | | Spring Return Open | Valve Normally Open | Actuators with One Switch | |
| | | | | VA9203-AGB-2Z | VA9203-GGB-2Z | VA9203-BGB-2 | VA9203-BUB-2 |
| VG1245AD | 1/2 | 1.2 ¹ | 200 | VG1245ADH923AGB | VG1245ADH923GGB | VG1245ADH923BGB | VG1245ADH923BUB |
| VG1245AE | | 1.9 ¹ | | VG1245AEH923AGB | VG1245AEH923GGB | VG1245AEH923BGB | VG1245AEH923BUB |
| VG1245AF | | 2.9 ¹ | | VG1245AFH923AGB | VG1245AFH923GGB | VG1245AFH923BGB | VG1245AFH923BUB |
| VG1245AG | | 4.7 ¹ | | VG1245AGH923AGB | VG1245AGH923GGB | VG1245AGH923BGB | VG1245AGH923BUB |
| VG1245AL | | 7.4 ¹ | | VG1245ALH923AGB | VG1245ALH923GGB | VG1245ALH923BGB | VG1245ALH923BUB |
| VG1245AN | | 11.7 | | VG1245ANH923AGB | VG1245ANH923GGB | VG1245ANH923BGB | VG1245ANH923BUB |
| VG1245BG | 3/4 | 4.7 ¹ | 200 | VG1245BGH923AGB | VG1245BGH923GGB | VG1245BGH923BGB | VG1245BGH923BUB |
| VG1245BL | | 7.4 ¹ | | VG1245BLH923AGB | VG1245BLH923GGB | VG1245BLH923BGB | VG1245BLH923BUB |
| VG1245BN | | 11.7 | | VG1245BNH923AGB | VG1245BNH923GGB | VG1245BNH923BGB | VG1245BNH923BUB |
| VG1245CL | 1 | 7.4 ¹ | 200 | VG1245CLH923AGB | VG1245CLH923GGB | VG1245CLH923BGB | VG1245CLH923BUB |
| VG1245CN | | 11.7 ¹ | | VG1245CNH923AGB | VG1245CNH923GGB | VG1245CNH923BGB | VG1245CNH923BUB |
| VG1245CP | | 18.7 | | VG1245CPH923AGB | VG1245CPH923GGB | VG1245CPH923BGB | VG1245CPH923BUB |
| Valve | Size, in. | Cv | Closeoff psig | Spring Return Open | Valve Normally Open | Actuators with Two Switches | |
| | | | | VA9208-AGC-3 | VA9208-GGC-3 | VA9208-BGC-3 | VA9208-BAC-3 |
| VG1245DN | 1-1/4 | 11.7 ¹ | 200 | VG1245DNH938AGC | VG1245DNH938GGC | VG1245DNH938BGC | VG1245DNH938BAC |
| VG1245DP | | 18.7 ¹ | | VG1245DPH938AGC | VG1245DPH938GGC | VG1245DPH938BGC | VG1245DPH938BAC |
| VG1245DR | | 29.2 | | VG1245DRH938AGC | VG1245DRH938GGC | VG1245DRH938BGC | VG1245DRH938BAC |
| VG1245EP | 1-1/2 | 18.7 ¹ | 200 | VG1245EPH938AGC | VG1245EPH938GGC | VG1245EPH938BGC | VG1245EPH938BAC |
| VG1245ER | | 29.2 ¹ | | VG1245ERH938AGC | VG1245ERH938GGC | VG1245ERH938BGC | VG1245ERH938BAC |
| VG1245ES | | 46.8 | | VG1245ESH938AGC | VG1245ESH938GGC | VG1245ESH938BGC | VG1245ESH938BAC |
| VG1245FR | 2 | 29.2 ¹ | 200 | VG1245FRH938AGC | VG1245FRH938GGC | VG1245FRH938BGC | VG1245FRH938BAC |
| VG1245FS | | 46.8 ¹ | | VG1245FSH938AGC | VG1245FSH938GGC | VG1245FSH938BGC | VG1245FSH938BAC |
| VG1245FT | | 73.7 | | VG1245FTH938AGC | VG1245FTH938GGC | VG1245FTH938BGC | VG1245FTH938BAC |
| Valve | Size, in. | Cv | Closeoff psig | Spring Return Closed | Valve Normally Closed | Actuators with One Switch | |
| | | | | VA9203-AGB-2Z | VA9203-GGB-2Z | VA9203-BGB-2 | VA9203-BUB-2 |
| VG1245AD | 1/2 | 1.2 ¹ | 200 | VG1245ADH943AGB | VG1245ADH943GGB | VG1245ADH943BGB | VG1245ADH943BUB |
| VG1245AE | | 1.9 ¹ | | VG1245AEH943AGB | VG1245AEH943GGB | VG1245AEH943BGB | VG1245AEH943BUB |
| VG1245AF | | 2.9 ¹ | | VG1245AFH943AGB | VG1245AFH943GGB | VG1245AFH943BGB | VG1245AFH943BUB |
| VG1245AG | | 4.7 ¹ | | VG1245AGH943AGB | VG1245AGH943GGB | VG1245AGH943BGB | VG1245AGH943BUB |
| VG1245AL | | 7.4 ¹ | | VG1245ALH943AGB | VG1245ALH943GGB | VG1245ALH943BGB | VG1245ALH943BUB |
| VG1245AN | | 11.7 | | VG1245ANH943AGB | VG1245ANH943GGB | VG1245ANH943BGB | VG1245ANH943BUB |
| VG1245BG | 3/4 | 4.7 ¹ | 200 | VG1245BGH943AGB | VG1245BGH943GGB | VG1245BGH943BGB | VG1245BGH943BUB |
| VG1245BL | | 7.4 ¹ | | VG1245BLH943AGB | VG1245BLH943GGB | VG1245BLH943BGB | VG1245BLH943BUB |
| VG1245BN | | 11.7 | | VG1245BNH943AGB | VG1245BNH943GGB | VG1245BNH943BGB | VG1245BNH943BUB |
| VG1245CL | 1 | 7.4 ¹ | 200 | VG1245CLH943AGB | VG1245CLH943GGB | VG1245CLH943BGB | VG1245CLH943BUB |
| VG1245CN | | 11.7 ¹ | | VG1245CNH943AGB | VG1245CNH943GGB | VG1245CNH943BGB | VG1245CNH943BUB |
| VG1245CP | | 18.7 | | VG1245CPH943AGB | VG1245CPH943GGB | VG1245CPH943BGB | VG1245CPH943BUB |
| Valve | Size, in. | Cv | Closeoff psig | Spring Return Closed | Valve Normally Closed | Actuators with Two Switches | |
| | | | | VA9208-AGC-3 | VA9208-GGC-3 | VA9208-BGC-3 | VA9208-BAC-3 |
| VG1245DN | 1-1/4 | 11.7 ¹ | 200 | VG1245DNH958AGC | VG1245DNH958GGC | VG1245DNH958BGC | VG1245DNH958BAC |
| VG1245DP | | 18.7 ¹ | | VG1245DPH958AGC | VG1245DPH958GGC | VG1245DPH958BGC | VG1245DPH958BAC |
| VG1245DR | | 29.2 | | VG1245DRH958AGC | VG1245DRH958GGC | VG1245DRH958BGC | VG1245DRH958BAC |
| VG1245EP | 1-1/2 | 18.7 ¹ | 200 | VG1245EPH958AGC | VG1245EPH958GGC | VG1245EPH958BGC | VG1245EPH958BAC |
| VG1245ER | | 29.2 ¹ | | VG1245ERH958AGC | VG1245ERH958GGC | VG1245ERH958BGC | VG1245ERH958BAC |
| VG1245ES | | 46.8 | | VG1245ESH958AGC | VG1245ESH958GGC | VG1245ESH958BGC | VG1245ESH958BAC |
| VG1245FR | 2 | 29.2 ¹ | 200 | VG1245FRH958AGC | VG1245FRH958GGC | VG1245FRH958BGC | VG1245FRH958BAC |
| VG1245FS | | 46.8 ¹ | | VG1245FSH958AGC | VG1245FSH958GGC | VG1245FSH958BGC | VG1245FSH958BAC |
| VG1245FT | | 73.7 | | VG1245FTH958AGC | VG1245FTH958GGC | VG1245FTH958BGC | VG1245FTH958BAC |

1. Cv has a characterizing disk.

VG1000 Series Two-Way, Stainless Steel Trim, NPT End Connections Ball Valves with Spring Return Electric Actuators with Switches (Continued)

Technical Specifications

| VG1000 Series Two-Way, Stainless Steel Trim Ball Valves with Spring Return Electric Actuators with Switches | | |
|---|---------------------|---|
| Service ¹ | | Hot Water, Chilled Water, 50/50 Glycol Solutions, and 15 psig (103 kPa) Saturated Steam for HVAC Systems (select models) |
| Fluid Temperature Limits | Water | -22 to 284°F (-30 to 140°C) |
| | Steam | 15 psig (103 kPa) at 250°F (121°C) |
| Maximum Actuator Fluid Temperature Limit | 212°F (100°C) | VA9203 VA9208 |
| | 284°F (140°C) | VA9203 with M9000-561 Thermal Barrier VA9208 with M9000-561 Thermal Barrier |
| Valve Body Pressure Rating | Water | 580 psig (3,999 kPa) at 203°F (95°C) 464 psig (3,199 kPa) at 284°F (140°C) (PN40) |
| | Steam | 15 psig (103 kPa) Saturated Steam (Only with VA9203 or VA9208 Series Actuator with M900-561 Thermal Barrier) |
| Maximum Closeoff Pressure | | 200 psig (1,378 kPa) |
| Maximum Recommended Operating Pressure Drop | | 50 psi Maximum Differential Pressure for Valves with Characterized Flow Control Disk and 30 psi Maximum for Quiet Service Ball Valves |
| Flow Characteristics | Two-Way | Equal Percentage |
| Rangeability ² | | Greater than 500:1 |
| Minimum Ambient Operating Temperature | -22°F (-30°C) | VA9203 Series Spring Return Actuators |
| | -40°F (-40°C) | VA9208 Series Spring Return Actuators |
| Maximum Ambient Operating Temperature ³ (Limited by the Actuator) | Direct Mount | 140°F (60°C): VA9203 or VA9208 Series Spring Return Actuators |
| Leakage | | 0.01% of Maximum Flow per ANSI/FCI 70-2, Class 4 |
| | | 1% of Maximum Flow for Three-Way Bypass Port |
| End Connections | | National Pipe Thread (NPT) |
| Materials | Body | Forged Brass |
| | Ball | 300 Series Stainless Steel |
| | Blowout-Proof Stem | 300 Series Stainless Steel |
| | Seats | Graphite-Reinforced PTFE with Ethylene Propylene Diene Monomer (EPDM) O-Ring Backing |
| | Stem Seals | EPDM Double O-Rings |
| | Characterizing Disk | Amodel® AS-1145HS Polyphthalamide Resin |

1. Proper water treatment is recommended; refer to the VDI 2035 Standard.
2. Rangeability is defined as the ratio of maximum controllable flow to minimum controllable flow.
3. In steam applications, install the valve with the stem horizontal to the piping and wrap the valve and piping with insulation.