


Job Name:

System Reference:

Date:




PAR-31MAA-J

SPECIFICATIONS:

- Controls group operation for up to 16 indoor units in a single group
- Features selectable multi-lingual LCD (English, Spanish, and French)
- Supports both Fahrenheit and Celsius
- User functions allow user to set
 - On/Off
 - Operation modes cool, heat, dry, fan
 - Set temperature
 - Fan speed setting
 - Airflow direction
- Timer Operation:
 - Weekly Timer: On/Off/Temperature setting up to 8 times per day of the week in 1-minute increments
 - Simple Timer: On and Off time can be set once within 72-hour period in 1-hour increments
 - Auto-off Timer: Turns indoor unit Off based on countdown time up to 4-hours in 30-minute increments
- Room Temperature: Displays room temperature sensed either at the indoor unit (default) or at the remote controller
- Set Temperature Range Limit: From the Backlit MA Controller, the allowable set temperature range can be reduced for cool and heat modes
- Supplemental heat function enable/disable
- Function Lock Out: Prohibits all functions or all functions except On/Off from the backlit MA controller
- Addressing: No addressing required
- Wiring: connects using two-wire, stranded, non-polar control wire to indoor unit connection terminal
- Dimensions: 4-3/4 x 3/4 x 4-3/4" (120 x 19 x 120 mm)

DIMENSIONS:


(Front view)



(Side view)

(Rear view)

Unit:mm[in.]



COOLING & HEATING

 1340 Satellite Boulevard, Suwanee, GA 30024
 Toll Free: 800-433-4822 www.mehvac.com