

MATERIAL SAFETY DATA SHEET 558 CA

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATIONS AND OF THE COMPANY UNDERTAKING

Product Name 558CA

Product Description Rubber Based Pressure Sensitive Adhesive

Manufacturer/Supplier Berry Plastics Corporation, Tapes and Coatings Division

Address 25 Forge Parkway

Franklin, MA 02038

Phone Number (800) 248-7659 (Monday – Friday 8:00 am to 5:00 pm)

Chemtrec Number (800) 424-9300
Revision Date: July 29, 2008
MSDS Date: January 12, 2007

Safety Data Sheet according to EC directive 2001/58/EC and OSHA's Hazcom Standard (29 CFR 1910.1200)

2. HAZARDS IDENTIFICATION

EU Main Hazards

Not classified as hazardous.

Routes of Entry

Skin contact

Carcinogenic Status

See Section 11 for information.

Target Organs

- Skin

Health Effects - Eyes

Contact may cause irritation due to mechanical abrasion.

Health Effects - Skin

Prolonged, repeated contact with adhesive may cause skin irritation.

Health Effects - Ingestion

Not an expected route of entry during normal handling and use.

Health Effects - Inhalation

Not expected to cause irritation during normal handling and use.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Component Name Polymers and Rubbers	CAS#/Codes N.A.	Concentration <30%	R Phrases None	Classification None
Hydrocarbon resin	N.A.	<25%	None	None
Zinc Oxide	1314-13-2 215-222-5	<2%	R50/53	N
Inorganic Compound(s)	N.A.	<30%	None	None
Titanium Dioxide	13463-67-7 236-675-5	<2%	None	None
Quartz	14808-60-7/ 238-878-4	<1%	None	None

Revision Date: July 29, 2008 Page 1 of 6

4. FIRST AID MEASURES

Eyes

Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Obtain medical attention if soreness or redness persists.

Skin

Wash skin thoroughly with soap and water. Obtain medical attention if blistering occurs or redness persists.

Ingestion

Obtain medical attention immediately.

Inhalation

Remove person to fresh air. Seek medical attention if symptoms persist.

Advice to Physicians

Treat symptomatically.

5. FIRE- FIGHTING MEASURES

Extinguishing Media

Water spray, carbon dioxide and dry chemical.

Unusual Fire and Explosion Hazards

Can release hazardous vapors during a fire.

Protective Equipment for Fire-Fighting

Wear full protective clothing and self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

No specific measures necessary. Prevent the material from entering drains or watercourses.

7. HANDLING AND STORAGE

Keep away from heat and sources of ignition. Exposure to high heat or flame can release irritating and toxic fumes. Storage area should be: - cool - dry - well ventilated - away from incompatible materials

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Standards

Exposure limits are listed below, if they exist.

Polymers and Rubbers

None established

Inorganic Compound(s)

None established

Hydrocarbon Resin

None established

Quartz

ACGIH TLV for Quartz (silica-crystalline) is 0.025 mg/m³ measured as respirable fraction of the aerosol

Zinc Oxide, fume

OSHA PEL 5 mg/m³ TWA

Zinc Oxide

ACGIH TLV: $2mg/m^3$ TWA, measured as respirable fraction of aerosol ACGIH STEL/CEIL: $10mg/m^3$, measured as respirable fraction of aerosol OSHA PEL(Dust only): $15mg/m^3$ total dust, $5mg/m^3$ respirable fraction

Revision Date: July 29, 2008 Page 2 of 6

8. **EXPOSURE CONTROLS/PERSONAL PROTECTION**

Titanium Dioxide

ACGIH TLV: 10 mg/m³ TWA OSHA PEL: 15 mg/m³ TWA (Total dust)

Engineering Control Measures

No specific measures necessary. Good general room ventilation is expected to be adequate to control

airborne levels.

Respiratory Protection

Respiratory protection not normally required.

Hand Protection

Not required under normal conditions of use. However, care should be taken to avoid contact with the adhesive.

Eye Protection

Safety glasses

Body Protection

Normal work wear.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State Metallized polymer and cloth backing with a rubber based pressure

sensitive adhesive

Color Light gray adhesive

Odor Slight

Hq Not applicable **Specific Gravity** No data available **Boiling Range/Point (°C/F)** Not applicable Not applicable Melting Point (°C/F) Not known Flash Point (PMCC) (°C/F)

Explosion Limits (%) No data available **Vapor Pressure** Not applicable

VOC (g/I) < 1 g/lDensity No data. Solubility in Water Not known Not applicable Vapor Density (Air = 1)

STABILITY AND REACTIVITY 10.

Stability

Stable under normal conditions.

Conditions to Avoid

- Heat - High temperatures

Materials to Avoid

Acids - bases - strong oxidizers

Hazardous Polymerization

Will not occur.

Hazardous Decomposition Products

- oxides of carbon - hydrocarbons - aldehydes - acrolein - waxes - oligomers - oxygenated hydrocarbons - ketones - irritating fumes

Revision Date: July 29, 2008 Page 3 of 6

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Low order of acute toxicity.

Chronic Toxicity/Carcinogenicity

Titanium Dioxide: IARC Overall Evaluation is 2B (Possibly carcinogenic to humans) When encapsulated in the adhesive matrix the risk of exposure is reduced.

For "inhalable" crystalline silica (quartz): IARC Overall Evaluation is 1 (carcinogenic to humans), the quartz in this formulation is in an adhesive matrix and is not expected to be "inhalable"

Genotoxicity

This product is not expected to cause any mutagenic effects.

Reproductive/Developmental Toxicity

This product is not expected to cause adverse reproductive effects.

12. ECOLOGICAL INFORMATION

Mobility

No relevant studies identified.

Persistence/Degradability

No relevant studies identified.

Bio-accumulation

No relevant studies identified.

Ecotoxicity

The product may be harmful to aquatic organisms.

13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with all applicable local and national regulations.

14. TRANSPORT INFORMATION

DOT CFR 172.101 Data UN Proper Shipping NameNot Regulated
Not Regulated

UN Class None.
UN Number None.
UN Packaging Group None.

Classification for AIR Consult current IATA Regulations prior to shipping by air.

Transportation (IATA)

15. REGULATORY INFORMATION

EU Label Information

Classification and labelling have been performed according to EU directives 67/548/EEC and 99/45/EC including amendments(2001/60/EC and 2006/8/EC)

EC Annex I Classification

According to EC Commission Directive 67/548/EEC this product is not classified.

R phrases

None.

S phrases

None.

Revision Date: July 29, 2008 Page 4 of 6

15. REGULATORY INFORMATION

US REGULATIONS (Federal, State) and INTERNATIONAL CHEMICAL REGISTRATION LAWS

TSCA Listing

This product contains ingredients that are listed on or exempt from listing on the EPA Toxic Substance Control Act Chemical Inventory.

EINECS Listing

All ingredients in this product have not been verified for inclusion on the European Inventory of Existing Commercial Chemical Substances (EINECS) or specifically exempted.

DSL (Canadian) Listing

All ingredients in this product have not been verified for inclusion on the Domestic Substance List (DSL).

California Proposition 65

This product contains the following materials which the State of California has found to cause cancer, birth defects or other reproductive harm: Arsenic (7440-38-2) <1ppm — Lead (7439-92-1) <1 - Formaldehyde (50-00-0) >50ppb

SARA Title III Sect. 311/312 Categorization

Immediate (acute) Delayed (chronic)

SARA Title III Sect. 313

This product contains the following chemicals that are listed in Section 313 at or above de minimis concentrations. Zinc Oxide (1314-13-2)

16. OTHER INFORMATION

NFPA Ratings

NFPA Code for Flammability - 0

NFPA Code for Health - 1

NFPA Code for Reactivity - 0

NFPA Code for Special Hazards – 0

HMIS Ratings

HMIS Code for Flammability - 0

HMIS Code for Health - 1

HMIS Code for Reactivity - 0

HMIS Code for Personal Protection - See Section 8

Abbreviations

N/A: Denotes no applicable information found or available

CAS#: Chemical Abstracts Service Number

ACGIH: American Conference of Governmental Industrial Hygienists

OSHA: Occupational Safety and Health Administration

TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
STEL: Short Term Exposure Limit
NTP: National Toxicology Program

IARC: International Agency for Research on Cancer

R: Risk S: Safety

LC50: Lethal Concentration 50%

LD50: Lethal Dose 50%

BOD: Biological Oxygen Demand

KoC: Soil Organic Carbon Partition Coefficient

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

N: Dangerous for the environment.

16. OTHER INFORMATION

For further Information email: msdstechnical@berryplastics.com

Prepared By: EnviroNet LLC.

The information and recommendations presented in this MSDS are based on sources believed to be accurate. Berry Plastics Corporation, Tapes and Coatings Division assumes no liability for the accuracy or completeness of this information. It is the user's responsibility to determine the suitability of the **material** for their particular purposes. In particular, we make NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, with respect to such information, and we assume no liability resulting from its use. Users should ensure that any use **or disposal** of the material is in accordance with applicable Federal, State, and local laws and regulations.

Revision Date: July 29, 2008 Page 6 of 6