



QC-STL PRO-4.8
QuietCool Stealth Pro Line

QC-STL PRO-4.8 Specifications

Motor Voltage	120 VAC, 60 Hz
Energy Use	Hi: 556 Watts / Med: 198 Watts / Low: 73 Watts
Air Flow	Hi:4718 CFM / Med:3247 CFM / Low:2200 CFM
HVI-916 Airflow	3881 CFM
Square Foot Coverage @ 2 CFM per SQ FT	Covers up to 2350 SQ FT
# of Speeds	3
Duct Diameter	18"
Duct Length	9 feet
Motor Head Diameter	18 1/2"
Motor Head Length	13 1/2"
Dampers	Barometric Pressurized R5 Dampers
Controls	Included 8 Hour Electronic Timer and Double 3-Way Switch
Warranty	15 Years
Framing	None Required
Joist Cutting	None Required; fits 16" or 24" on center
Minimum Suggested Attic Venting	6.3 SQ FT net free area
Ceiling Rough Opening	14 1/4" x 30 1/4"
Removable Grille Outside Dimension	16" x 32"
Shipping Weight	64 lbs.
Box Dimensions	40" x 22" x 36"
In The Box	<ul style="list-style-type: none"> -QC STL PRO-4.8 Motorhead -Removable Grille -Cut-out Template -Window Locks -Damper Box -9 Foot Duct -Accessory Bag -Controls



For more information, visit our website at:
QUIETCOOLSYSTEMS.COM