

QC-STL PRO-6.5 Specifications

	1	
Motor Voltage	120 VAC, 60 Hz	
Energy Use	Hi/Hi: 569 Watts / Hi/Lo: 344 Watts Hi/Off: 266 Watts / Lo/Off: 76 Watts	
Air Flow	Hi: 6035 CFM / Med/Hi: 4897 CFM Med/Low: 3630 CFM / Low: 2323 CFM	
HVI-916 Airflow	5660 CFM	
Square Foot Coverage @ 2 CFM per SQ FT	Covers up to 3050 SQ FT	
# of Speeds	4	
Duct Diameter	16"	
Duct Length	6 feet	
Motor Head Diameter	16 1/2"	
Motor Head Length	13 1/2"	
Dampers	Barometric Pressurized R5 Dampers	
Controls	Included 8 Hour Electronic Timer and Double	
	3-Way Switch	
Warranty	15 Years	
Framing	None Required	
Joist Cutting	None Required; fits 16" or 24" on center	
Minimum Suggested Attic Venting	8.0 SQ FT net free area	
Ceiling Rough Opening	14 1/4" x 36 1/4"	
Removable Grille Outside Dimension	16" x 38"	
Shipping Weight	87 lbs.	
Box Dimensions	42" x 20" x 38"	
In The Box	-QC STL PRO-6.5 Motorhead	-Damper Box
	-Removable Grille	-6 Foot Duct(2)
	-Cut-out Template	-Accessory Bag(2)
	-Window Locks	-Controls

