



## QC STL PRO-1.5X Specifications

Motor Voltage	120 VAC, 60 Hz	
Energy Use	66.7 Watts	
Air Flow	1479 CFM	
HVI-916 Airflow (for CA Title 24 New Construction)	1040 CFM	
dBA	Hi: 37.2	
Recommended SQFT Coverage @ 2 CFM per SQ FT	Covers up to 740 SQ FT	
# of Speeds	1	
Duct Diameter	14"	
Duct Length	6 feet	
Motor Head Diameter	14 1/2"	
Motor Head Length	13 1/2"	
Dampers	Barometric Pressurized R5 Dampers	
Controls	Included 8 Hour Electronic Timer	
Warranty	15 Years	
Framing	None Required	
Joist Cutting	None Required; fits 16" or 24" on center	
Minimum Suggested Attic Venting	1.98 SQ FT net free area	
Ceiling Rough Opening	14 1/4" x 14 1/4"	
Removable Grille Outside Dimension	16" x 16"	
Shipping Weight	43 lbs.	
Box Dimensions	20" x 20" x 38"	
In The Box	-QC STL PRO-1.5X Motorhead	-Damper Box
	-Removable Grille	-6 Foot Duct
	-Cut-out Template	-Accessory Bag
	-Window Locks	-Controls

