

SUBMITTAL COVER SHEET

PROJECT NAME	
LOCATION	
ARCHITECT	
ENGINEER	
CONTRACTOR	
SUBMITTED BY	DATE
	UNIT SUMMARY
Quantity	
Unit Designation	
Model No.	
Total Cooling	
Sensible Cooling	
Air Ent. Evaporator	
Air Lvg. Evaporator	
Heating Input	
Heating Output	
CFM/ESP	
EER/SEER	
Electrical	
Minimum Ampacity	
MinMax. Breaker	
Net Unit Weight	
Accessory	
Catalog Form Number	
ACCESSORIES:	NOTES:

(-)APM- JEZ SERIES – AIR CONDITIONERS EFFICIENCIES TO 16 SEER/13 EER NOMINAL SIZES 1.5-5 TONS [5.28-17.6 kW]

JOB NAME			UNIT MODEL NO
CONTRACTOR			COIL MODEL NO
ENGINEER			AIR HANDLER MODEL NO
SUBMITTED FOR	☐ APPROVAL	□ RECORD	LOCATION
DATE			ORDER NO

UNIT DATA

EFFICIENCY SEER TOTAL CAPACITY MBH [kW] SENSIBLE CAPACITY MBH [kW] OUTDOOR DESIGN TEMP °F [°C] DB TEMP. OF AIR ENTERING EVAPORATOR COIL °F [°C] DB — °F [°C] WB

SUPPLY AIR BLOWER PERFORMANCE

TOTAL AIR SUPPLY	CFM [L/s]
TOTAL RESISTANCE EXTERNAL TO UNIT	IWC
MOTOR RATING	HP [W]

ELECTRICAL DATA

POWER SUPPLY	Hz
MINIMUM WIRE SIZE	AWG
MAXIMUM OVERCURRENT DEVICE FUSES/HACR BREAKER	AMPS

CLEARANCES

ACCESS SIDE	24" [609.6 mm]	
AIR INLETS	6" [152 mm]	
ABOVE UNIT	60" [1524 mm]	

Featuring the Comfort Control System™

- Increased Reliability
- On-Board Diagnostics
- Fault Recall
- Active Protection™

FEATURES FOR (-)APM- JEZ SERIES

- The Comfort Control System™ provides on-board diagnostics and fault history for condensing units with single-phase compressors by detecting system and electrical problems without adding sensors. It can also communicate "fault codes" to enabled "L terminal" thermostats. The integrated diagnostics with Active Protection™ prevents compressor operation when potentially harmful conditions are detected.
- Features an exclusive 7-Segment LED Display. The information display quickly and accurately shows technicians the source of malfunctions.
- Compressor sound blanket is standard to provide quiet operation.
- R410-A Refrigerant
- High Efficiency
- Scroll Compressor
- All refrigerant connections are on the exterior of the unit, located close to the ground for neat appearing installations.
- Powder painted galvanized steel cabinet. The full wrap-around louvered grille protects the coil from damage.
- Copper tube—aluminum fin coils are used on all models.
- The control box is located in the top corner of the cabinet providing for easy access through a service panel.
- Service valves are standard on all models.
- Power and control wiring are kept separate.
- Separate compressor compartment for easy service access.
- Drawn, painted base pan for extra corrosion resistance and sound reduction.
- The automatic high and low pressure controls, and hard start components are standard.
- The filter drier is standard on all models.
- Certified and rated under AHRI Standard 210.
- U.L. and cUL listed.
- Factory limited warranty on all parts as follows:

Conditional Compressor (Registration Required)Ten (10) Years
PartsTen (10) Years

(-)APM- JEZ Series Conditional Replacement Warranty:

Manufacturer will provide a replacement model (if an exact replacement is not available, an equivalent product will be provided) to the original purchaser if the compressor fails within 5 years. See product warranty card for additional information.

FIELD INSTALLED ACCESSORIES


Low Ambient Control	⊏	
Compressor Crankcase Heater		l












DIMENSIONS

Model Number (-)APM-	Height "H" (Inches) [mm]	Length "L" (Inches) [mm]	Width "W" (Inches) [mm]
018JEZ	19 [483]	401/2 [1029]	275/8 [702]
024JEZ/030JEZ	29 [737]	443/8 [1127]	311/2 [800]
036JEZ/042JEZ 048JEZ/056JEZ/060JEZ	33 [838]	443/8 [1127]	311/2 [800]

[] Designates Metric Conversions



SPECIAL NOTES ON EQUIPMENT:

Before proceeding with installation, refer to installation instructions packaged with each model, as well as complying with all Federal, State, Provincial, and Local codes, regulations, and practices.

Rheem Sales Company, Inc. P.O. Box 17010, Fort Smith, AR 72917

"In keeping with its policy of continuous progress and product improvement, Rheem reserves the right to make changes without notice."

PRINTED IN U.S.A. 10-12 QG FORM NO. X33-1405